



RF 5 CHANNEL RECEIVER CONTROLLER SERIES

PROJECT:
PREPARED BY:
DATE:
TYPE:



FEATURE

- Compatible with LB2834-5C-US and LB2858Z4-5C
- 5 channel full functional constant voltage RF LED controller available with 12-36VDC and max. 5A per channel output
- Enables to drive RGB and dual color (warm white and cold white) LED lighting with a single receiver while pairing with a RGB & CCT remote
- Full compatibility with a variety of monochrome, dual color, RGB/RGBW and RGB+CCT RF remotes
- Multiple zones can be controlled separately or synchronously with unlimited receivers in each zone
- Each receiver can be controlled by 8 different remotes max.
- Can be WiFi controlled by app installed on IOS or Android mobile devices while working with WiFi-RF converter
- Brightness of each R, G, B and W are fully adjustable.

PERFORMANCE

• Input Voltage	12-36 VDC	• Waterproof Grade	IP20
• Output Current	5x5A	• Connector Current Rating	Max. 20A
• Output Power	5x (60-180)W	• Radio Frequency	869.5/434/916.5MHz
• Remarks	Constant Voltage	• Dimensions	6.69" x 2.32" x 1.14"

ORDERING GUIDE

Model	Channel	Prorocol	Environment	Finish
LB56110	5 Channel (RGBWW)	RF	Dry	White





RF 5 CHANNEL RECEIVER

CONTROLLER SERIES

PROJECT:

PREPARED BY:

DATE:

TYPE:

DIMENSION

