



EDGE LIT UNIVERSAL EXIT SIGN

EXIT SIGN SERIES

PROJECT:

PREPARED BY:

DATE:

TYPE:



FEATURE

- Recessed housing with hanger bar.
- Aluminum housing with high grade acrylic panel.
- Replaceable acrylic EXIT panel.
- Removable directional indicators.
- Single and double face universal design.
- Removable front cover for easy installation & maintenance.
- 8" height red exit sign.
- Suitable for damp location.
- Compact and decorative design

ELECTRICAL

- 120/277 VAC dual voltage operation.
- Test switch and charge rate indicator.
- Self test and Self diagnostics function is available for battery backup model.
- Fully automatic, solid state charger.
- Brown out circuit with overload and
- Short Circuit protection.

PERFORMANCE

• Wattage	4W	• Environment	Damp Location
• Rated Life	50,000 hrs.	• Mounting	Recessed / Surface
• Input Voltage	120V/277V	• Warranty	2 yrs.
• Input Frequency	60Hz	• Dimensions (Clear Glass)	14" x 9½"
• Operating Temperatures	10°-40°C		

ORDERING GUIDE

Model	Wattage	Description
LB91600	4W	Universal Mount Edge Lit Exit Sign
LB91605	4W	Optional Part - Clear Glass





EDGE LIT UNIVERSAL EXIT SIGN

EXIT SIGN SERIES

PROJECT:

PREPARED BY:

DATE:

TYPE:

DIMENSION

