



# 4FT STAIRCASE FIXTURE

LINEAR SERIES

PROJECT:

PREPARED BY:

DATE:

TYPE:



## PERFORMANCE

- Available with emergency battery back up, motion sensor, or a combination of the two.
- Flicker free
- Cold-rolled steel body with white power coating
- High diffusion light-milky polycarbonate diffuser
- Flush mount application

## PERFORMANCE

• Wattage	38W	• THD	<20%
• Lumen	5000LM	• Power Factor	>0.95
• Efficacy	110LM/W	• CRI	>80
• CCT	3000K/3500K/4000K Selectable	• Input Current	0.21A - 0.09A
• Input Power	120V-277V	• Frequency	60Hz
• Dimming	0-10V / Triac Dimming	• Lifetime	50,000hrs

## DIMENSIONS

- Size 4.5" x 3.625"

## INSTALLATION

• Environment	Damp Location	• Operation Temperature	-20 °C to 50 °C
• IP Rating	IP44		

## ORDER GUIDE

Model	Length	Wattage	Lumen	Color Temperature	Configuration
LB85170	4FT	38W	5000LM	30K/35K/40K Selectable	No Add On
LB85170-MS					Motion Sensor
LB85170-EM					Emergency Battery
LB85170-EMB-MS					Emergency Battery + Motion Sensor



# 4FT STAIRCASE FIXTURE

LINEAR SERIES

PROJECT:

PREPARED BY:

DATE:

TYPE:

## DIMENSION

