


LED STRIP LIGHT 3W/FT



PROJECT: PREPARED BY: DATE: TYPE:

3W/FT


Neon

The Neon Horizontal Bend LED Strip is a flexible, IP67rated lighting solution designed for smooth, sidebending installations. Built with high-efficacy 2835 SMD chips, it delivers up to 335 lumens per foot with a CRI of 90+, ideal for outlining curves, coves, and architectural edges with a soft, uniform glow. Its fully encapsulated body ensures durability in indoor and outdoor environments, while factory-sealed custom cuts and multiple cable outlet directions support tailored project needs

Ideal for ambient lighting applications, this solution delivers a soft yet effective glow-perfect for cove details, ceiling integrations, and layered architectural compositions

PERFORMANCE			
• Wattage	3W/FT	• Maximum Run	16.4FT
• Input Power	24V	 Certification 	UL / ETL
• CRI	90+	• Dimming	Triac
• LED Chip	Neon	• Warranty	5 years
DIMENSIONS			
• Length per Roll	16.4FT		
• Height x Width	0.39" x 0.39"		
INSTALLATION			
• Environment	IP67	• Adhesive	ЗМ
• Cutting Interval	3.93"	Ambient Temperature	-20°C to 40°

Ambient Lighting



718-475-2515


www.lightblueusa.com

Information on Spec sheets or other supportive files may be modified at any given time



LED STRIP LIGHT 3W/FT

PROJECT: PREPARED BY: DATE: TYPE:



ORDER GUIDE

Model	Length (ft)	Wattage	ССТ	Lumens/FT	Efficacy	IP Rating
LB53529	16.4FT	3W/FT	2700K	308LM	101LM/W	IP67
LB53530	16.4FT	3W/FT	3000K	320LM	105LM/W	IP67
LB53531	16.4FT	3W/FT	3500K	326LM	107LM/W	IP67
LB53532	16.4FT	3W/FT	4000K	335LM	110LM/W	IP67

• All cuts must be made directly on line indication

• Any cuts made in field must be properly sealed in order to be IP67 rated


718-475-2515




LED STRIP LIGHT 3W/FT

PROJECT: PREPARED BY: DATE: TYPE:

DIMENSION AND OUTLET DIRECTION








LED STRIP LIGHT 3W/FT

PROJECT: PREPARED BY: DATE: TYPE:

ACCESSORIES

LB53537 - Clear End Cap




LB53536 - Coupling




LB53540 - End Straight



LB53541 - End side left



LB53542 - End side right



LB53543 - End bottom



LB53539 - Aluminum Buckle 12Â 12.5Â 25mm LengthS Buckle crew 1000mm 4pcs 4pcs Screw 15â 3.5mm LB53538 - Aluminum Profile 12â 12.5â 2440mm LengthS crew Aluminum 2440mm 10pcs profile Screw Τã 15â 3.5mm 15m



LED STRIP LIGHT 3W/FT

COMPATIBLE DIRVER

PROJECT: PREPARED BY: DATE: TYPE:



Model	LB55500
Wattage	120W
Dimensions	7.4" x 3.7" x 1.7"
Temperature	IP67
Dimming	Triac/MLV/ELV



Model	LB55501
Wattage	200W
Dimensions	9.4" x 4" x 1.7"
Temperature	IP20
Dimming	Triac/MLV/ELV



Model	LB55502
Wattage	300W
Dimensions	10" x 4.3" x 1.7"
Temperature	IP20
Dimming	Triac/MLV/ELV



Model	LB55460
Wattage	30W
Dimensions	12" x 2.4" x 1.4"
Temperature	IP67
Dimming	Triac/MLV/ELV



Model	
Wattage	
Dimensions	
Temperature	
Dimming	

LB55462 60W 12" x 2.4" x 1.4" IP67 Triac/MLV/ELV



Model
Wattage
Dimensions
Temperature
Dimming


LB55464 96W 12" x 2.4" x 1.4" IP67 Triac/MLV/ELV



LED STRIP LIGHT 3W/FT

PROJECT: PREPARED BY: DATE: TYPE:

INSTALLATION ACCESSORIES



www.lightblueusa.com