

LED STRIP LIGHT 3W/FT



PROJECT: PREPARED BY: DATE: TYPE:

# 3W/FT

#### Neon

The Neon Vertical Bend LED Strip is a flexible, IP67rated lighting solution designed for smooth, topbending installations. Built with high-efficacy 2835 SMD chips, it delivers up to 335 lumens per foot with a CRI of 90+, ideal for outlining curves, coves, and architectural edges with a soft, uniform glow. Its fully encapsulated body ensures durability in indoor and outdoor environments, while factory-sealed custom cuts and multiple cable outlet directions support tailored project needs

Ideal for ambient lighting applications, this solution delivers a soft yet effective glow—perfect for cove details, ceiling integrations, and layered architectural compositions

· Wattage 3W/FT · Maximum Run 16.4F   · Input Power 24V · Certification UL / ET   · CRI 90+ · Dimming Tria   · LED Chip Neon · Warranty 5 yea   DIMENSIONS 16.4FT
· CRI90+· DimmingTrian· LED ChipNeon· Warranty5 yeaDIMENSIONS
LED Chip Neon · Warranty 5 yea
DIMENSIONS
Longth new Dell 16 4FT
• Length per Roll 16.4FT
• Height x Width 0.39" x 0.39"
INSTALLATION
• Environment IP67 • Adhesive 3
• Cutting Interval 3.29" • Ambient Temperature -20°C to 40

Ambient Lighting



186 Van Dyke Street - Brooklyn, NY 11231

Light Blue USA & Associates LLC www.ligh

www.lightblueusa.com

Revision Date 5/15/25



LED STRIP LIGHT 3W/FT

PROJECT: PREPARED BY: DATE: TYPE:



### ORDER GUIDE

Model	Length (ft)	Wattage	ССТ	Lumens/FT	Efficacy	IP Rating
LB53509	16.4FT	3W/FT	2700K	222LM	91LM/W	IP67
LB53510	16.4FT	3W/FT	3000K	290LM	95LM/W	IP67
LB53512	16.4FT	3W/FT	3500K	296LM	97LM/W	IP67
LB53511	16.4FT	3W/FT	4000K	305LM	100LM/W	IP67

• All cuts must be made directly on line indication

• Any cuts made in field must be properly sealed in order to be IP67 rated



LED STRIP LIGHT 3W/FT

PROJECT: PREPARED BY: DATE: TYPE:

## DIMENSION AND OUTLET DIRECTION







LED STRIP LIGHT 3W/FT

## PROJECT: PREPARED BY: DATE: TYPE:

## **CONNECTIG ACCESSORIES**

LB53537 - Clear End Cap







LB53540 - End Straight



#### LB53541 - End side left



#### LB53542 - End side right



#### LB53543 - End bottom



LB53539 - Aluminum Buckle 12Â 12.5Â 25mm LengthS Buckle crew T T 1000mm 4pcs 4pcs Screw 15â 3.5mm LB53538 - Aluminum Profile 12â 12.5â 2440mm LengthS crew Aluminum 2440mm 10pcs profile Screw Τ ..... 15â 3.5mm 15m

186 Van Dyke Street - Brooklyn, NY 11231

m 718-475-2515



LED STRIP LIGHT 3W/FT

## COMPATIBLE DIRVER

PROJECT: PREPARED BY: DATE: TYPE:



Model	LB55500
Wattage	120W
Dimensions	7.4" x 3.7" x 1.7"
Temperature	IP67
Dimming	Triac/MLV/ELV



Model	LB55501
Wattage	200W
Dimensions	9.4" x 4" x 1.7"
Temperature	IP20
Dimming	Triac/MLV/ELV



Model	LB55502
Wattage	300W
Dimensions	10" x 4.3" x 1.7"
Temperature	IP20
Dimming	Triac/MLV/ELV



Model	LB55460
Wattage	30W
Dimensions	12" x 2.4" x 1.4"
Temperature	IP67
Dimming	Triac/MLV/ELV



Model
Wattage
Dimensions
Temperature
Dimming

LB55462 60W 12" x 2.4" x 1.4" IP67 Triac/MLV/ELV



Model
Wattage
Dimensions
Temperature
Dimming

LB55464 96W 12" x 2.4" x 1.4" IP67 Triac/MLV/ELV

718-475-2515



LED STRIP LIGHT 3W/FT

PROJECT: PREPARED BY: DATE: TYPE:

#### INSTALLATION ACCESSORIES

