


LED STRIP LIGHT 3W/FT

PROJECT:
PREPARED BY:

DATE:

TYPE:





# 3W/FT

#### Neon

The Neon Vertical Bend LED Strip is a flexible, IP67-rated lighting solution designed for smooth, top-bending installations. Built with high-efficacy 2835 SMD chips, it delivers up to 335 lumens per foot with a CRI of 90+, ideal for outlining curves, coves, and architectural edges with a soft, uniform glow. Its fully encapsulated body ensures durability in indoor and outdoor environments, while factory-sealed custom cuts and multiple cable outlet directions support tailored project needs

Ideal for ambient lighting applications, this solution delivers a soft yet effective glow—perfect for cove details, ceiling integrations, and layered architectural compositions

## **PERFORMANCE**

 Wattage 3W/FT · Maximum Run 16.4FT · Input Power 24V Certification UL / ETL · CRI 90+ Dimming Triac • LED Chip 2835 Warranty 5 years

#### **DIMENSIONS**


• Length per Roll 16.4FT

• Height x Width 0.39" x 0.39"

## **INSTALLATION**

• Environment IP67 • Adhesive 3M

• Cutting Interval 3.29" • Ambient Temperature -20°C to 40°



Light Blue USA & Associates LLC www.lightblueusa.com 718-475-2515




LED STRIP LIGHT 3W/FT

PROJECT:

PREPARED BY:

DATE:

TYPE:



## **ORDER GUIDE**

Model	Length (ft)	Wattage	ССТ	Lumens/FT	Efficacy	IP Rating
LB53509	16.4FT	3W/FT	2700K	222LM	91LM/W	IP67
LB53510	16.4FT	3W/FT	3000K	290LM	95LM/W	IP67
LB53512	16.4FT	3W/FT	3500K	296LM	97LM/W	IP67
LB53511	16.4FT	3W/FT	4000K	305LM	100LM/W	IP67

- · All cuts must be made directly on line indication
- · Any cuts made in field must be properly sealed in order to be IP67 rated



LED STRIP LIGHT 3W/FT


PROJECT:


PREPARED BY:

DATE:

TYPE:

## **DIMENSION AND OUTLET DIRECTION**







LED STRIP LIGHT 3W/FT

PROJECT:

PREPARED BY:

DATE:

TYPE:

## **CONNECTIG ACCESSORIES**


LB53537 - Clear End Cap





LB53536 - Coupling





LB53540 - End Straight





LB53541 - End side left





LB53542 - End side right





LB53543 - End bottom





#### LB53539 - Aluminum Buckle


12Â 12.5Â 25mm

Screw 15å 3.5mm






LengthS	Buckle	crew
1000mm	4pcs	4pcs






## LB53538 - Aluminum Profile



	LengthS	crew	
Aluminum profile	2440mm	10pcs	





186 Van Dyke Street - Brooklyn, NY 11231

Light Blue USA & Associates LLC

www.lightblueusa.com

718-475-2515

Revision Date 5/15/25



LED STRIP LIGHT 3W/FT

## **COMPATIBLE DIRVER**

PROJECT:
PREPARED BY:

DATE:

TYPE:



ModelLB55500Wattage120WDimensions7.4" x 3.7" x 1.7"TemperatureIP67DimmingTriac/MLV/ELV



Model LB55460
Wattage 30W
Dimensions 12" x 2.4" x 1.4"
Temperature IP67
Dimming Triac/MLV/ELV



ModelLB55501Wattage200WDimensions9.4" x 4" x 1.7"TemperatureIP20DimmingTriac/MLV/ELV



ModelLB55462Wattage60WDimensions12" x 2.4" x 1.4"TemperatureIP67DimmingTriac/MLV/ELV



Model LB55502
Wattage 300W
Dimensions 10" x 4.3" x 1.7"
Temperature IP20
Dimming Triac/MLV/ELV



Model LB55464
Wattage 96W
Dimensions 12" x 2.4" x 1.4"
Temperature IP67
Dimming Triac/MLV/ELV



LED STRIP LIGHT 3W/FT

PROJECT:


PREPARED BY:

DATE:

TYPE:


## **INSTALLATION ACCESSORIES**

#### Light Profile




## **Bending Direction**






#### Correct Bending Way



Face to the light surface fold the strip, the minimum bending diameter is 100mm.



Light surface upwards, the strip is bendable to right or left naturally, the minimum bending diameter is 100mm.

#### Incorrect Bending Way



Face to the side surface (as the picture shows) . Do not bend sideward to damage the strip .



Face to the side surface (as the picture shows). Do not bend upward to damage the strip.



(as the picture shows) please do not twist the strip, or it will be damaged.