
UNIVERSAL MOUNT EDGE LIT EXIT SIGN EXIT SIGN SERIES



LBUSA



FEATURES

 Recessed housing with hanger bar. 	Removable front cover for easy installation & maintenance	
 Aluminum housing with high grade acrylic panel. 	 8" height red exit sign. 	
Replaceable acrylic EXIT panel.	Suitable for damp location.	
Removable directional indicators.	 Compact and decorative design 	
Single and double face universal design.		
ELECTRICAL		
120/277 VAC dual voltage operation.	Fully automatic, solid state charger.	
 Test switch and charge rate indicator. 	 Brown out circuit with overload and 	
Self test and Self diagnostics function is available for battery	Short Circuit protection.	
backup model.		
MOUNTING		
Recessed mounting	Universal mounting including wall mount, side mounting,	
Surface mounting	and ceiling mounting	
SPECIFICATIONS		
• Wattage	• Operating Temperatures 10°-40	

Wattage	4W	 Operating Temperatures 	10°-40°C
Rated Life	50,000 hrs.	Environment	Damp Location
Input Voltage	120V/277V	Warranty	2 yrs.
Input Frequency	60Hz	 Dimensions for the glass 	14" x 9½"

ORDERING GUIDE

Model	Description
LB91600	Universal Mount Edge Lit Exit Sign
LB91605	Optional Part- Clear Glass

