



ROUND SLIM DOWNLIGHT FIRE RATED
DOWNLIGHT SERIES

PROJECT:
PREPARED BY:
DATE:
TYPE:



FEATURE

- 2 Hour Fire Rated Without additional housing or hardware
- Heat Resistant Casing Provides up to 2 hours fire protection
- Heavy Duty Steel Spring Clips for easy installation
- Plenum Rated Cable For commercial installations
- Class 2, Class P, Type HL, CE, UL, FCC compliant
- Connection Box Comes with Junction Box & Driver, No Housing Required.
- CRI 90+
- 2700K, 3000K, 3500K, 4000K, 5000K Selectable

PERFORMANCE

• Applications	Multi-Family Residential, Basements & Commercial	• Environment	Damp
• Wattage	9W	• Cable	FT6 / CMP Plenum Rated
• CCT	2700K,3000K,3500K,4000K,5000K Selectable	• Air Tight	Yes
• Lumen	900LM	• Finish	White, Black, Satin Nickel
• Halogen Equivalent	156W	• Ambient Temperature	-20°C to 40°C
• Beam Angle	120°	• Lifetime	50,000hrs
• CRI	90+	• Warranty	5 Years
• Input Voltage	120VAC 50/60Hz	• Fire Rating	UL 263-2011(R2022), STM E119-20 & CAN/ULC-S101-14
• Dimming	Triac 10% - 100%		

ORDERING GUIDE

Model	Wattage	Color Temperature	Accessories	EM
LB11451	9W (900LM)	5CCT 27K/30K/35K/40K/50K 5CCT Selectable	FGP Flanged Plate with Hanger Bars Model FRP 26" Flat Rough-In Plates MFP 13" Mounting Plate Flat UMP Universal Mounting New Construction Plate	MFP Tenmat Fire Rated Light Cover FRB IC Fire Rated Box





ROUND SLIM DOWNLIGHT FIRE RATED

DOWNLIGHT SERIES

PROJECT:
PREPARED BY:
DATE:
TYPE:

ACCESSORIES



Flanged Plate with Hanger
Bars Model



26" Flat Rough-In Plates



13" Mounting Plate Flat



Universal Mounting New
Construction Plate



Tenmat Fire Rated
Light Cover



IC Fire Rated Box



ROUND SLIM DOWNLIGHT FIRE RATED
DOWNLIGHT SERIES

PROJECT:
PREPARED BY:
DATE:
TYPE:

DIMENSION

