



TEMPORARY LED HIGH BAY LIGHT
COMMERICAL LIGHTING SERIES

PROJECT:
PREPARED BY:
DATE:
TYPE:



FEATURE

- 6KV Surge Protection, lamp can bear sudden high voltage.
- Stainless steel guard for impact protection.
- 10ft 16AWG cord with plug suitable to huge construction area.
- Damp location rated.
- Hidden & built-in connector design

PERFORMANCE

• Wattage	100W	• Operating Temperature	-40-45°C
• Input Current	>0.9	• Cord Length	10ft
• Input Voltage	120-277V*	• Beam Angle	360°
• Delivered Light Output	14000LM	• IP Rating	IP65
• Surge Voltage	6000V	• Lamp Life	50,000 hrs.
• CCT	5000K	• Dimensions	6.1" x 11.2"
• CRI	>80	• Warranty	5 Years
• Linkable QTY	8pcs		

ORDERING GUIDE

Model	Wattage	Lumens (Delivered)	Environment
LB74103	100W	14000LM	Wet

*120V only Power Plug Provided with fixture, 277V Hardwired only



TEMPORARY LED HIGH BAY LIGHT
COMMERICAL LIGHTING SERIES

PROJECT:
PREPARED BY:
DATE:
TYPE:

DIMENSION

