
LED OUTDOOR WALL LIGHT

LED Outdoor Wall Light Cylinder with Light Up / Down square massive modern design shape provides a high-powered illumination. It's a perfect choice for any exteriors. This energy efficient fixture made of Die-casting Aluminum body with protecting Glass lens, creates a clear and bright lighting. . Suitable for wet locations, with moisture, weather, corrosion, and outdoor contaminant proof. The direction of lights keeps them out of neighbors' windows, at the same time perfectly illuminating the around area. Perfect for patio, porch, corridor, backyard, garage, garden, walkway outdoor lighting. Easy and fast installation, no bulb replacement required.



Finish:


BLACK


OIL RUBBED BRONZE


WHITE


PACKAGE CONTENTS:

Part	Description	Q-ty
-	LED Outdoor Wall Light Cylinder	1
Α	Wire nuts	3
В	Outlet box screws	2
-	Вох	1
-	Installation Instructions	1









A WARNING

RISK OF PERSONAL INJURY – PLEASE READ THESE INSTRUCTIONS CAREFULLY. FOLLOW ALL INSTALLATION INSTRUCTIONS AND OBSERVE ALL WARNINGS.

Make sure the "supply" voltage corresponds to the "rated" product voltage 120V 60Hz

Retain these instructions. Note: If you are an installer, please give these instructions to the property owner for future reference.

Risk of injury: Always wear the necessary safety equipment to prevent injuries when opening, handling, installing and maintaining this product

Risk of electrical shock: This product must be installed in accordance with the applicable installation code by a professional familiar with the construction and operation of the product. The professional should also be aware of, and understand the hazards involved with the installation of this product.

Risk of Fire: Always consult with a qualified electrician to ensure the correct branch circuit conductor is utilized. The minimum conductor rating requirement is 90°C (194°F) in order to be code compliant.

Assembly Instructions

Step 1 – Preparing for installation.

- A. Disconnect electrical power at fuse or circuit breaker box before installing or servicing any part of this fixture.
- B. Remove fixture from carton; remove components from hardware kit.
- C. Remove the mounting bracket (4) from the fixture (1).
- D. Install mounting bracket (4) to junction box (not provided) by tighten two screws(2) to secure it.

Wiring-all wiring must take place inside junction box (not included).

Step 2 – Wiring fixture.

- A. Make all wire connections to appropriate wire. Secure with wire nuts (provided).
- B. Connect the bare wire from the fixture and the supply power source ground wire.
- C. Connect the black wire from the fixture to the black (L) wire from supply power source.
- D. Connect the white wire from the fixture to the white (N) wire from supply power source.
- E. Pull on each wire lead to make sure connections are secure. Make certain no bare wires are exposed outside of wire connectors. Tuck all connections neatly into the junction box.

Step 3 – Mounting.

A.Install fixture (1) to mounting bracket (4) by tighten two screws (3) on top and bottom to secure it.

B. After mounting the fixture, caulk the suface between the fixture back and the mounting surface.

Step 4 – Restore power at fuse or circuit breaker box.

